

# MAXCALIBER

## Double Magnet Series



MODELS	CONFIGURATION	POWER	Fs	Qes	Qms	Qts	Sd Sq.cm	Mms	Xmax (mm)	Vas	BI (Tm)	F.Range	No%	PARALLEL RDC Ohm	DUAL RDC Ohm	SERIES RDC Ohm	ENCLOSURE
CA10900/2/2 10"	1 Ohm (parallel) or 2 Ohm x 2 DVC	450wrms 900peak	27Hz	0.38	6.9	0.36	333	168g	+/- 10	31.5L/ 1.1cu.ft	7.8	<200Hz	.17	0.8	1.6 x 2 coils		P/BP 4th & 6th order
CA10900/2/2 10"	4 Ohm (2 Ohm x 2 in series)	450wrms 900peak	27Hz	0.34	6.2	0.32	333	168g	+/- 10	31.5L/ 1.1cu.ft	16.6	<200Hz	.20			3.2	P/BP 5th order
CA10900/4/4 10"	2 Ohm (parallel) or 2 Ohm x 2 DVC	450wrms 900peak	27Hz	0.40	6.7	0.40	333	164g	+/- 10	28.3L/ 1.0cu.ft	10.2	<200Hz	.17	1.5	3 x 2 coils		P/BP 5th order
CA10900/4/4 10"	8 Ohm (4 Ohm x 2 in series)	450wrms 900peak	27Hz	0.36	6.0	0.38	333	164g	+/- 10	28.3L/ 1.0cu.ft	23	<200Hz	.20			6.0	P/BP 5th order
CA121000/2/2 12"	1 Ohm (parallel) or 2 Ohm x 2 DVC	500wrms 1000peak	22Hz	0.40	6.7	0.38	502	214g	+/- 13	77.8L/ 2.7cu.ft	7.8	<200Hz	.24	0.8	1.6 x 2 coils		P/BP 5th order
CA121000/2/2 12"	4 Ohm (2 Ohm x 2 in series)	500wrms 1000peak	22Hz	0.30	6.3	0.37	502	214g	+/- 13	77.8L/ 2.7cu.ft	15.6	<200Hz	.24			3.2	P/BP 5th order
CA121000/4/4 12"	2 Ohm (parallel) or 2 Ohm x 2 DVC	500wrms 1000peak	22Hz	0.42	6.5	0.43	502	192g	+/- 13	74L/ 2.6cu.ft	11.2	<200Hz	.23	1.5	3 x 2 coils		P/BP 5th order
CA121000/4/4 12"	8 Ohm (4 Ohm x 2 in series)	500wrms 1000peak	22Hz	0.41	6.1	0.42	502	192g	+/- 13	74L/ 2.6cu.ft	22	<200Hz	.26			6.0	P/BP 5th order
CA151600/2/2 15"	1 Ohm (parallel) or 2 Ohm x 2 DVC	800wrms 1600peak	21Hz	0.44	8.5	0.42	800	268g	+/- 12	157L/ 5.5cu.ft	8.1	<150Hz	.44	0.725	1.45 x 2 coils		S/P/BP 4th & 5th order
CA151600/2/2 15"	4 Ohm (2 Ohm x 2 in series)	800wrms 1600peak	21Hz	0.34	6.7	0.32	800	268g	+/- 12	157L/ 5.5cu.ft	18.3	<150Hz	.57			2.9	S/P/BP 4th & 5th order
CA151600/4/4 15"	2 Ohm (parallel) or 2 Ohm x 2 DVC	800wrms 1600peak	22Hz	0.47	7.6	0.45	800	268g	+/- 12	144L/ 5cu.ft	11.3	<200Hz	.42	1.5	3 x 2 coils		S/P/BP 4th & 5th order
CA151600/4/4 15"	8 Ohm (4 Ohm x 2 in series)	800wrms 1600peak	22Hz	0.36	6.4	0.35	800	268g	+/- 12	144L/ 5cu.ft	26	<200Hz	.55			6.0	S/P/BP 4th & 5th order

LEGEND: "S" Sealed enclosure, "P" Ported enclosure, "BP" Band Pass enclosure

Specifications are subject to change without notice

For information and ordering:

RMD Audio

Tel: (01933) 676211

e-mail: sales@rmdaudio.co.uk, www.rmdaudio.co.uk

**RMD**  
automotive audio design and installations