

# MAXCALIBER

## Single Magnet Series



MODELS	CONFIGURATION	POWER	Fs	Qes	Qms	Qts	Sd Sq.cm	Mms	Xmax (mm)	Vas	BI (Tm)	F.Range	No%	PARALLEL RDC Ohm	DUAL RDC Ohm	SERIES RDC Ohm	ENCLOSURE
CA10700/2/2 10"	1 Ohm (parallel) or 2 Ohm x 2 DVC	350wrms 700peak	29Hz	0.47	7.0	0.44	333	136g	+/- 8.5	33.5L/ 1.2cu.ft	6.3	<300Hz	.19	0.725	1.45 x 2 Ohm coils		S/P/BP 4th & 6th order
CA10700/2/2 10"	4 Ohm (2 Ohm x 2 in series)	350wrms 700peak	29Hz	0.39	5.9	0.37	333	136g	+/- 8.5	33.5L/ 1.2cu.ft	9.2	<300Hz	.22			2.9	S/P/BP 4th & 6th order
CA10700/4/4 10"	2 Ohm (parallel) or 2 Ohm x 2 DVC	350wrms 700peak	29Hz	0.50	6.3	0.46	333	129g	+/- 8.5	29.5L/ 1.0cu.ft	6.6	<300Hz	.22	1.45	2.9 x 2 Ohm coils		S/P/BP 4th & 6th order
CA10700/4/4 10"	8 Ohm (4 Ohm x 2 in series)	350wrms 700peak	29Hz	0.42	6.0	0.40	333	129g	+/- 8.5	29.5L/ 1.0cu.ft	13.5	<300Hz	.22			5.8	S/P/BP 4th & 6th order
CA12700/2/2 12"	1 Ohm (parallel) or 2 Ohm x 2 DVC	350wrms 700peak	23Hz	0.52	5.9	0.47	502	146g	+/- 8.5	99.3L/ 3.5cu.ft	5.0	<300Hz	.38	0.725	1.5 x 2 Ohm coils		S/P/BP 4th & 6th order
CA12700/2/2 12"	4 Ohm (2 Ohm x 2 in series)	350wrms 700peak	23Hz	0.43	5.2	0.40	502	146g	+/- 8.5	99.3L/ 3.5cu.ft	10.4	<300Hz	.42			2.9	S/P/BP 4th & 6th order
CA12700/4/4 12"	2 Ohm (parallel) or 2 Ohm x 2 DVC	350wrms 700peak	23Hz	0.54	5.7	0.49	502	136g	+/- 8.5	96.1L/ 3.4cu.ft	6.0	<300Hz	.31	1.45	2.9 x 2 Ohm coils		S/P/BP 4th & 6th order
CA12700/4/4 12"	8 Ohm (4 Ohm x 2 in series)	350wrms 700peak	23Hz	0.46	4.9	0.46	502	136g	+/- 8.5	96.1L/ 3.4cu.ft	12.3	<300Hz	.37			5.8	S/P/BP 4th & 6th order

LEGEND: "S" Sealed enclosure, "P" Ported enclosure, "BP" Band Pass enclosure

Specifications are subject to change without notice

For information and ordering:  
RMD Audio  
Tel: (01933) 676211  
e-mail: sales@rmdaudio.co.uk, www.rmdaudio.co.uk

**RMD**  
automotive audio design and installations