

# MAXPENTIVENT



MODELS	POWER	Fs	Qes	Qms	Qts	Sd Sq.cm	Mms	Xmax mm	Vas	F.Range	4 Ohm DCR	8 Ohm DCR	MAGNET	VOICE COIL	No%	ENCLOSURE
<b>PV-0411</b> <b>4"</b>	55wrms	68Hz	0.73	5.9	0.65	55	6.9g	+/-2.5	0.74L/ .026cu.ft	<7kHz	3.1	5.7	11oz	1"K2	.143	<b>S / P</b>
<b>PV-0511</b> <b>5 1/2"</b>	60wrms	64Hz	0.83	6.9	0.74	92	8.39g	+/-2.5	7.9L/ .28cu.ft	<6kHz	3.1	5.6	11oz	1"K2	.17	<b>S / P</b>
<b>PV-6520</b> <b>6 1/2"</b>	80wrms	43Hz	0.38	7.1	0.36	139	18g	+/-3.5	20L/ .7cu.ft	<5kHz	3.0	5.6	20oz	1"K4	.42	<b>S / P</b>
<b>PV-0820</b> <b>8"</b>	100wrms	34Hz	0.83	7.2	0.75	241	28g	+/-3.5	52L/ 1.8cu.ft	<4.5kHz	3.0	5.9	20oz	1.5"K2	.24	<b>S / P</b>
<b>PV-1030</b> <b>10"</b>	125wrms	19Hz	0.37	3.6	0.35	360	61g	+/-4	130L/ 4.6cu.ft	<2kHz	2.9	5.6	30oz	1.5"K4	.4	<b>S / P BP</b> <b>4 6</b>
<b>PV-1050</b> <b>10"</b>	240wrms	28Hz	0.37	7.9	0.35	360	92g	+/-6	61.7L/ 2.2cu.ft	<1kHz	3.1	5.6	50oz	2"K4	.38	<b>P / BP</b> <b>6</b>
<b>PV-1230</b> <b>12"</b>	125wrms	20Hz	0.51	4.0	0.45	531	78g	+/-4	317L/ 11.1cu.ft	<1.8kHz	2.9	5.6	30oz	1.5"K4	.51	<b>S / P / BP</b> <b>4</b>
<b>PV-1250</b> <b>12"</b>	275wrms	21Hz	0.35	5.9	0.33	531	94g	+/-6	238L/ 8.4cu.ft	<1kHz	3.1	5.6	50oz	2"K4	.65	<b>P / BP</b> <b>6</b>
<b>PV-1550</b> <b>15"</b>	275wrms	24Hz	0.75	7.9	0.69	845	72g	+/-6	592L/ 21cu.ft	<1kHz	3.1	5.6	50oz	2"K4	1.14	<b>S / P / BP</b> <b>4 6 F</b>

LEGEND: "S" Sealed enclosure, "P" Ported enclosure, "BP" Band Pass enclosure

Specifications are subject to change without notice

For information and ordering:

RMD Audio

Tel: (01933) 676211

e-mail: sales@rmdaudio.co.uk, www.rmdaudio.co.uk

**RMD**  
automotive audio design and installations